

MULTI-FUNCTIONAL FLEXIBILITY

GR SERIES GRAPPLES

Secondary Demolition and Recycling

Our advanced lines of premiere demolition equipment continue to grow: introducing the GR Grapples Series. Built with steel for maximum strength, they are extremely resistant to wear-and-tear while making easy work of handling materials such as wood and bricks. They are also ideal for facilitating recycling. Additional highlights of this exciting new line include:

- A 360° hydraulic rotation to guarantee precision placement.
- A hydraulic cylinder synchronized to a piston rod system for facilitating homogeneous movement.
- Interchangeable blades.



MODEL GR		GR3	GR5	GR7	GR10	GR15	GR20	GR25	GR30	GR40
GRAPPLE OPENING	mm	1050	1140	1650	1760	1885	2025	2200	2400	3000
	in.	41	45	65	69	74	80	87	95	118
GRAPPLE WIDTH	mm	400	500	700	800	1000	1200	1400	1500	1500
	in.	16	20	27.5	31.5	39.5	47	55	59	59
TOOL HEIGHT	mm	800	840	1290	1480	1525	1610	1700	1800	2300
	in.	32	33	51	58	60	63	67	71	90
EXCAVATOR WEIGHT	Ton	2,5/4	4/10	9/14	14/18	17/22	22/30	30/50	35/60	50/65
	lbs	5511 / 8818	8818 / 22046	19842 / 30864	30864 / 48502	37479 / 48502	48502 / 66139	66139 / 110231	77162 / 132277	110231 / 143300
WEIGHT	Kg	250	370	760	1040	1380	1780	2450	2800	3500
	lbs	551	815	1675	2293	3042	3924	5401	6173	7716
OIL PRESSURE	Bar	200	200	250	300	300	300	300	300	330
	psi	2900	2900	3626	4351	4351	4351	4351	4351	4786
OIL CAPACITY	L/min	25	25	50	50	50	50	60	120	150
	gal/min	6	6	13	13	13	13	16	32	40
ROTATION OIL PRESSURE	Bar	20	20	60	60	60	60	60	100	100
	psi	290	290	870	870	870	870	870	1450	1450
ROTATION OIL CAPACITY	L/min	2	2	25	30	30	30	40	40	60
	gal/min	0.53	0.53	6.6	8	8	8	11	11	16
HYDRAULIC ROTATION		360°	360°	360°	360°	360°	360°	360°	360°	360°